

Shipping Weights and Dimensions

Model GPA

Electric Motor Driven Fire Pump Controller

Full Service

Full Voltage Across The Line Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx. Shipping Weight | |
|----------------|---------|---|-------|-------|-------------|-------|-------|-------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 75-150 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 200 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 220-240 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 75-200 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 250 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 380-415 | 5-60 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 75-125 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 150-300 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 350-450 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 440-480 | 5-60 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 75-150 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 200-400 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 450-500 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 600 | 5-75 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 100-150 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 200-500 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx. Shipping Weight | |
|----------------|-------------|---|-------|-------|-------------|-------|-------|-------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 380-415 | 4-45 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 55-110 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 132-250* | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 315 and up* | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPA + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Full Voltage Across The Line Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 40-60 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 75-100 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 125-150 | 76 | 70 | 27 | 1930 | 1778 | 686 | 750 | 340 |
| | 200 | 76 | 82 | 27 | 1930 | 2083 | 686 | 850 | 386 |
| 220-240 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 280 | 127 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 390 | 177 |
| | 75-125 | 76 | 64 | 27 | 1930 | 1626 | 686 | 450 | 204 |
| | 150-200 | 76 | 70 | 27 | 1930 | 1778 | 686 | 750 | 340 |
| | 250 | 76 | 82 | 27 | 1930 | 2083 | 686 | 850 | 386 |
| 380-415 | 5-60 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 75-125 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 150-200 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 250-350 | 76 | 82 | 27 | 1930 | 2083 | 686 | 900 | 408 |
| | 400-450 | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |
| 440-480 | 5-60 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 75-150 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 200-250 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 300-450 | 76 | 700 | 27 | 1930 | 17780 | 686 | 900 | 408 |
| | 500 | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |
| 600 | 5-75 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 100-150 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 200-350 | 76 | 64 | 27 | 1930 | 1626 | 686 | 900 | 408 |
| | 400-500 | 76 | 70 | 27 | 1930 | 1778 | 686 | 1100 | 499 |

Shipping Weights and Dimensions

Model GPA + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Full Voltage Across The Line Starter

With ViZiTouch V2 Operator Interface

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|----------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 380-415 | 4-45 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 55-110 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 132 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 200-315* | 76 | 82 | 27 | 1930 | 2083 | 686 | 900 | 408 |
| | 315* | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPP

Electric Motor Driven Fire Pump Controller

Full Service

Reduced Voltage Part Winding Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|---------|---------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 75-150 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 200 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 220-240 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 75-200 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 250 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| | 300-350 | 76 | 70 | 27 | 1930 | 1778 | 686 | 500 | 227 |
| 380-415 | 5-60 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 75-125 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 150-300 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 350-450 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 440-480 | 5-60 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 75-150 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 200-400 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 450-500 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 600 | 5-75 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 100-150 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 200-500 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|---------|-------------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 380-415 | 4-45 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 55-110 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 132-250* | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 315 and up* | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPP + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Reduced Voltage Part Winding Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 40-60 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 75-100 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 125-150 | 76 | 70 | 27 | 1930 | 1778 | 686 | 750 | 340 |
| | 200 | 76 | 82 | 27 | 1930 | 2083 | 686 | 850 | 386 |
| 220-240 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 283 | 128 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 390 | 177 |
| | 75-125 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 150-200 | 76 | 70 | 27 | 1930 | 1778 | 686 | 750 | 340 |
| | 250 | 76 | 82 | 27 | 1930 | 2083 | 686 | 850 | 386 |
| 380-415 | 5-60 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 75-125 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 150-200 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 250-350 | 76 | 82 | 27 | 1930 | 2083 | 686 | 900 | 408 |
| | 400-450 | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |
| 440-480 | 5-60 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 75-150 | 62 | 54 | 23 | 1575 | 1372 | 584 | 391 | 177 |
| | 200-250 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 300-450 | 76 | 70 | 27 | 1930 | 1778 | 686 | 900 | 408 |
| | 500 | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |
| 600 | 5-75 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 100-150 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 200-350 | 76 | 64 | 27 | 1930 | 1626 | 686 | 900 | 408 |
| | 400-500 | 76 | 70 | 27 | 1930 | 1778 | 686 | 1100 | 499 |

Shipping Weights and Dimensions

Model GPP + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Reduced Voltage Part Winding Starter

With ViZiTouch V2 Operator Interface

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|----------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 380-415 | 4-45 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 55-110 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 132 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 200-315* | 76 | 82 | 27 | 1930 | 2083 | 686 | 900 | 408 |
| | 315* | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPY

Electric Motor Driven Fire Pump Controller

Full Service

Reduced Voltage Y-Delta Open Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|---------|---------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 75-150 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 200 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 220-240 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 225 | 102 |
| | 75-200 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 250 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 380-415 | 5-60 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 75-125 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 150-300 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 350-450 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 440-480 | 5-60 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 75-150 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 200-400 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 450-500 | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |
| 600 | 5-75 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 100-150 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 200-500 | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|---------|-------------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 380-415 | 4-45 | 56 | 30 | 21 | 1422 | 762 | 533 | 170 | 77 |
| | 55-110 | 62 | 34 | 23 | 1575 | 864 | 584 | 230 | 104 |
| | 132-250* | 76 | 40 | 27 | 1930 | 1016 | 686 | 400 | 181 |
| | 315 and up* | 76 | 46 | 27 | 1930 | 1168 | 686 | 450 | 204 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPY + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Reduced Voltage Y-Delta Open Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 40-60 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 75-100 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 125-150 | 76 | 70 | 27 | 1930 | 1778 | 686 | 750 | 340 |
| | 200 | 76 | 82 | 27 | 1930 | 2083 | 686 | 850 | 386 |
| 220-240 | 5-30 | 56 | 30 | 21 | 1422 | 762 | 533 | 283 | 128 |
| | 40-60 | 62 | 34 | 23 | 1575 | 864 | 584 | 390 | 177 |
| | 75-125 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 150-200 | 76 | 70 | 27 | 1930 | 1778 | 686 | 750 | 340 |
| | 250 | 76 | 82 | 27 | 1930 | 2083 | 686 | 850 | 386 |
| 380-415 | 5-60 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 75-125 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 150-200 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 250-350 | 76 | 82 | 27 | 1930 | 2083 | 686 | 900 | 408 |
| | 400-450 | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |
| 440-480 | 5-60 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 75-150 | 62 | 54 | 23 | 1575 | 1372 | 584 | 391 | 177 |
| | 200-250 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 300-450 | 76 | 70 | 27 | 1930 | 1778 | 686 | 900 | 408 |
| | 500 | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |
| 600 | 5-75 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 100-150 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 200-350 | 76 | 64 | 27 | 1930 | 1626 | 686 | 900 | 408 |
| | 400-500 | 76 | 70 | 27 | 1930 | 1778 | 686 | 1100 | 499 |

Shipping Weights and Dimensions

Model GPY + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Reduced Voltage Y-Delta Open Starter

With ViZiTouch V2 Operator Interface

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|----------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 380-415 | 4-45 | 56 | 46 | 21 | 1422 | 1168 | 533 | 280 | 127 |
| | 55-110 | 62 | 54 | 23 | 1575 | 1372 | 584 | 390 | 177 |
| | 132 | 76 | 64 | 27 | 1930 | 1626 | 686 | 650 | 295 |
| | 200-315* | 76 | 82 | 27 | 1930 | 2083 | 686 | 900 | 408 |
| | 315* | 76 | 82 | 27 | 1930 | 2083 | 686 | 1100 | 499 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPS

Electric Motor Driven Fire Pump Controller

Full Service

Reduced Voltage Electronic Soft Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 208 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 200 | 91 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 290 | 132 |
| | 75-125 | 76 | 46 | 29 | 1930 | 1168 | 737 | 415 | 188 |
| | 150 | 76 | 64 | 29 | 1930 | 1626 | 737 | 430 | 195 |
| | 200 | 76 | 70 | 29 | 1930 | 1778 | 737 | 750 | 340 |
| 220-240 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 200 | 91 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 290 | 132 |
| | 75-150 | 76 | 46 | 29 | 1930 | 1168 | 737 | 415 | 188 |
| | 200 | 76 | 64 | 29 | 1930 | 1626 | 737 | 430 | 195 |
| | 250 | 76 | 70 | 29 | 1930 | 1778 | 737 | 550 | 249 |
| 380-415 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 200 | 91 |
| | 75-125 | 62 | 40 | 23 | 1575 | 1016 | 584 | 292 | 132 |
| | 150-250 | 76 | 46 | 29 | 1930 | 1168 | 737 | 415 | 188 |
| | 300 | 76 | 64 | 29 | 1930 | 1626 | 737 | 645 | 293 |
| | 350-450 | 76 | 70 | 29 | 1930 | 1778 | 737 | 750 | 340 |
| 440-480 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 200 | 91 |
| | 75-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 320 | 145 |
| | 200-300 | 76 | 46 | 29 | 1930 | 1168 | 737 | 420 | 191 |
| | 350-400 | 76 | 64 | 36 | 1930 | 1626 | 914 | 700 | 318 |
| | 450-500 | 76 | 70 | 29 | 1930 | 1778 | 737 | 850 | 386 |
| 600 | 5-75 | 56 | 36 | 21 | 1422 | 914 | 533 | 200 | 91 |
| | 100-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 280 | 127 |
| | 200-350 | 76 | 46 | 29 | 1930 | 1168 | 737 | 450 | 204 |
| | 400-500 | 76 | 64 | 29 | 1930 | 1626 | 737 | 800 | 363 |

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|--------------|---|----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 380-415 | 4-45 | 56 | 36 | 21 | 1422 | 914 | 533 | 200 | 91 |
| | 55-110 | 62 | 40 | 23 | 1575 | 1016 | 584 | 292 | 132 |
| | 132-200 | 76 | 46 | 29 | 1930 | 1168 | 737 | 415 | 188 |
| | 250* | 76 | 64 | 29 | 1930 | 1626 | 737 | 645 | 293 |
| | 315 and up * | 76 | 70 | 29 | 1930 | 1778 | 737 | 750 | 340 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPS + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full service

Reduced Voltage Electronic Soft Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|-----|----|-------------|------|------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 208 | 5-30 | 56 | 52 | 21 | 1422 | 1321 | 533 | 300 | 136 |
| | 40-60 | 62 | 60 | 23 | 1575 | 1524 | 584 | 460 | 209 |
| | 75-100 | 76 | 70 | 36 | 1930 | 1778 | 914 | 850 | 386 |
| | 125 | 76 | 76 | 36 | 1930 | 1930 | 914 | 850 | 386 |
| | 150 | 76 | 94 | 36 | 1930 | 2388 | 914 | 1065 | 483 |
| | 200 | 76 | 112 | 36 | 1930 | 2845 | 914 | 1500 | 680 |
| 220-240 | 5-30 | 56 | 52 | 21 | 1422 | 1321 | 533 | 300 | 136 |
| | 40-60 | 62 | 60 | 23 | 1575 | 1524 | 584 | 460 | 209 |
| | 75-125 | 76 | 70 | 36 | 1930 | 1778 | 914 | 750 | 340 |
| | 150 | 76 | 76 | 36 | 1930 | 1930 | 914 | 1065 | 483 |
| | 200 | 76 | 100 | 36 | 1930 | 2540 | 914 | 1500 | 680 |
| | 250 | 76 | 112 | 36 | 1930 | 2845 | 914 | 950 | 431 |
| 380-415 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 335 | 152 |
| | 75-125 | 62 | 60 | 23 | 1575 | 1524 | 584 | 600 | 272 |
| | 150-200 | 76 | 70 | 36 | 1930 | 1778 | 914 | 800 | 363 |
| | 250 | 76 | 76 | 36 | 1930 | 1930 | 914 | 900 | 408 |
| | 300-350 | 76 | 100 | 36 | 1930 | 2540 | 914 | 1300 | 590 |
| | 400-450 | 76 | 112 | 36 | 1930 | 2845 | 914 | 1300 | 590 |
| 440-480 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 335 | 152 |
| | 75-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 465 | 211 |
| | 200-250 | 76 | 70 | 36 | 1930 | 1778 | 914 | 800 | 363 |
| | 300 | 76 | 76 | 36 | 1930 | 1930 | 914 | 900 | 408 |
| | 350-450 | 76 | 100 | 41 | 1930 | 2540 | 1041 | 1150 | 522 |
| | 500 | 76 | 100 | 41 | 1930 | 2540 | 1041 | 1500 | 680 |
| 600 | 5-75 | 56 | 52 | 21 | 1422 | 1321 | 533 | 330 | 150 |
| | 100-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 450 | 204 |
| | 200-350 | 76 | 70 | 36 | 1930 | 1778 | 914 | 750 | 340 |
| | 400 | 76 | 94 | 41 | 1930 | 2388 | 1041 | 1150 | 522 |
| | 450-500 | 76 | 100 | 41 | 1930 | 2540 | 1041 | 1500 | 680 |

Shipping Weights and Dimensions

Model GPS + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full service

Reduced Voltage Electronic Soft Starter

With ViZiTouch V2 Operator Interface

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|--------|---|-----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 380-415 | 4-45 | 56 | 52 | 21 | 1422 | 1321 | 533 | 335 | 152 |
| | 55-110 | 62 | 60 | 23 | 1575 | 1524 | 584 | 600 | 272 |
| | 132 | 76 | 70 | 36 | 1930 | 1778 | 914 | 800 | 363 |
| | 200 | 76 | 76 | 36 | 1930 | 1930 | 914 | 900 | 408 |
| | 250 | 76 | 100 | 36 | 1930 | 2540 | 914 | 1300 | 590 |
| | 315* | 76 | 112 | 36 | 1930 | 2845 | 914 | 1300 | 590 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPR

Electric Motor Driven Fire Pump Controller

Full Service

Reduced Voltage Autotransformer Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 208 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 220 | 100 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 350 | 159 |
| | 75-150 | 76 | 46 | 29 | 1930 | 1168 | 737 | 530 | 240 |
| | 200 | 76 | 70 | 29 | 1930 | 1778 | 737 | 650 | 295 |
| 220-240 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 220 | 100 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 350 | 159 |
| | 75-200 | 76 | 46 | 29 | 1930 | 1168 | 737 | 530 | 240 |
| | 250 | 76 | 70 | 29 | 1930 | 1778 | 737 | 650 | 295 |
| 380-415 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 310 | 141 |
| | 75-125 | 62 | 40 | 23 | 1575 | 1016 | 584 | 425 | 193 |
| | 150-300 | 76 | 46 | 29 | 1930 | 1168 | 737 | 765 | 347 |
| | 350-450 | 76 | 70 | 29 | 1930 | 1778 | 737 | 1800 | 816 |
| 440-480 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 230 | 104 |
| | 75-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 380 | 172 |
| | 200-450 | 76 | 46 | 29 | 1930 | 1168 | 737 | 1900 | 862 |
| | 500 | 76 | 70 | 29 | 1930 | 1778 | 737 | 2000 | 907 |
| 600 | 5-75 | 56 | 36 | 21 | 1422 | 914 | 533 | 230 | 104 |
| | 100-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 450 | 204 |
| | 200-500 | 76 | 46 | 29 | 1930 | 1168 | 737 | 335 | 152 |

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|-------------|---|----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 380-415 | 4-45 | 56 | 36 | 21 | 1422 | 914 | 533 | 310 | 141 |
| | 55-110 | 62 | 40 | 23 | 1575 | 1016 | 584 | 425 | 193 |
| | 132-250* | 76 | 46 | 29 | 1930 | 1168 | 737 | 765 | 347 |
| | 315 and up* | 76 | 70 | 29 | 1930 | 1778 | 737 | 1800 | 816 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPR + GPU

Electric Motor Driven Fire Pump Controller

With automatic power transfer switch

Full service

Reduced voltage autotransformer starter

With ViZiTouch V2 operator interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|-----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 208 | 5-30 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 40-60 | 62 | 60 | 23 | 1575 | 1524 | 584 | 510 | 231 |
| | 75-100 | 76 | 70 | 27 | 1930 | 1778 | 686 | 815 | 370 |
| | 125-150 | 76 | 76 | 27 | 1930 | 1930 | 686 | 850 | 386 |
| | 200 | 76 | 112 | 21 | 1930 | 2845 | 533 | 1150 | 522 |
| 220-240 | 5-30 | 56 | 52 | 23 | 1422 | 1321 | 584 | 345 | 156 |
| | 40-60 | 62 | 60 | 27 | 1575 | 1524 | 686 | 510 | 231 |
| | 75-125 | 76 | 70 | 27 | 1930 | 1778 | 686 | 900 | 408 |
| | 150-200 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1200 | 544 |
| | 250 | 76 | 112 | 27 | 1930 | 2845 | 686 | 1350 | 612 |
| 380-415 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 400 | 181 |
| | 75-125 | 62 | 60 | 23 | 1575 | 1524 | 584 | 700 | 318 |
| | 150-200 | 76 | 70 | 27 | 1930 | 1778 | 686 | 1050 | 476 |
| | 250-300 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1200 | 544 |
| | 350 | 76 | 100 | 27 | 1930 | 2540 | 686 | 1300 | 590 |
| | 400-450 | 76 | 112 | 27 | 1930 | 2845 | 686 | 1400 | 635 |
| 440-480 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 75-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 570 | 259 |
| | 200-250 | 76 | 70 | 27 | 1930 | 1778 | 686 | 1120 | 508 |
| | 300-450 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1350 | 612 |
| | 500 | 76 | 112 | 27 | 1930 | 2845 | 686 | 1500 | 680 |
| 600 | 5-75 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 100-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 600 | 272 |
| | 200-350 | 76 | 70 | 27 | 1930 | 1778 | 686 | 995 | 451 |
| | 400-500 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1400 | 635 |

Shipping Weights and Dimensions

Model GPR + GPU

Electric Motor Driven Fire Pump Controller

With automatic power transfer switch

Full service

Reduced voltage autotransformer starter

With ViZiTouch V2 operator interface

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|-------------|---|-----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 380-415 | 4-45 | 56 | 52 | 21 | 1422 | 1321 | 533 | 400 | 181 |
| | 55-110 | 62 | 60 | 23 | 1575 | 1524 | 584 | 700 | 318 |
| | 132 | 76 | 70 | 27 | 1930 | 1778 | 686 | 1050 | 476 |
| | 250 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1200 | 544 |
| | 315* | 76 | 100 | 27 | 1930 | 2540 | 686 | 1400 | 635 |
| | 315 and up* | 76 | 112 | 27 | 1930 | 2845 | 686 | N/A | N/A |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPW

Electric Motor Driven Fire Pump Controller

Full Service

Reduced Voltage Y-Delta Closed Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 208 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 220 | 100 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 350 | 159 |
| | 75-150 | 76 | 46 | 29 | 1930 | 1168 | 737 | 530 | 240 |
| | 200 | 76 | 70 | 29 | 1930 | 1778 | 737 | 650 | 295 |
| 220-240 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 220 | 100 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 350 | 159 |
| | 75-200 | 76 | 46 | 29 | 1930 | 1168 | 737 | 530 | 240 |
| | 250 | 76 | 70 | 29 | 1930 | 1778 | 737 | 650 | 295 |
| 380-415 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 310 | 141 |
| | 75-125 | 62 | 40 | 23 | 1575 | 1016 | 584 | 425 | 193 |
| | 150-300 | 76 | 46 | 29 | 1930 | 1168 | 737 | 765 | 347 |
| | 350-450 | 76 | 70 | 29 | 1930 | 1778 | 737 | 1800 | 816 |
| 440-480 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 230 | 104 |
| | 75-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 380 | 172 |
| | 200-450 | 76 | 46 | 29 | 1930 | 1168 | 737 | 1900 | 862 |
| | 500 | 76 | 70 | 29 | 1930 | 1778 | 737 | 2000 | 907 |
| 600 | 5-75 | 56 | 36 | 21 | 1422 | 914 | 533 | 230 | 104 |
| | 100-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 450 | 204 |
| | 200-500 | 76 | 46 | 29 | 1930 | 1168 | 737 | 335 | 152 |

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|-------------|---|----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 380-415 | 4-45 | 56 | 36 | 21 | 1422 | 914 | 533 | 310 | 141 |
| | 55-110 | 62 | 40 | 23 | 1575 | 1016 | 584 | 425 | 193 |
| | 132-250* | 76 | 46 | 29 | 1930 | 1168 | 737 | 765 | 347 |
| | 315 and up* | 76 | 70 | 29 | 1930 | 1778 | 737 | 1800 | 816 |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPW + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Reduce Voltage Y-Delta Closed Starter

With ViZiTouch V2 operator interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|---------|---|-----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 208 | 5-30 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 40-60 | 62 | 60 | 23 | 1575 | 1524 | 584 | 510 | 231 |
| | 75-100 | 76 | 70 | 27 | 1930 | 1778 | 686 | 850 | 386 |
| | 125-150 | 76 | 76 | 27 | 1930 | 1930 | 686 | 850 | 386 |
| | 200 | 76 | 112 | 21 | 1930 | 2845 | 533 | 1150 | 522 |
| 220-240 | 5-30 | 56 | 52 | 23 | 1422 | 1321 | 584 | 345 | 156 |
| | 40-60 | 62 | 60 | 27 | 1575 | 1524 | 686 | 510 | 231 |
| | 75-125 | 76 | 70 | 27 | 1930 | 1778 | 686 | 900 | 408 |
| | 150-200 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1200 | 544 |
| | 250 | 76 | 112 | 27 | 1930 | 2845 | 686 | 1350 | 612 |
| 380-415 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 400 | 181 |
| | 75-125 | 62 | 60 | 23 | 1575 | 1524 | 584 | 700 | 318 |
| | 150-200 | 76 | 70 | 27 | 1930 | 1778 | 686 | 850 | 386 |
| | 250-300 | 76 | 76 | 27 | 1930 | 1930 | 686 | 850 | 386 |
| | 350 | 76 | 100 | 27 | 1930 | 2540 | 686 | 850 | 386 |
| | 400-450 | 76 | 112 | 27 | 1930 | 2845 | 686 | 850 | 386 |
| 440-480 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 75-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 570 | 259 |
| | 200-250 | 76 | 70 | 27 | 1930 | 1778 | 686 | 850 | 386 |
| | 300-450 | 76 | 76 | 27 | 1930 | 1930 | 686 | 850 | 386 |
| | 500 | 76 | 112 | 27 | 1930 | 2845 | 686 | 850 | 386 |
| 600 | 5-75 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 100-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 600 | 272 |
| | 200-350 | 76 | 70 | 27 | 1930 | 1778 | 686 | 995 | 451 |
| | 400-500 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1400 | 635 |

Shipping Weights and Dimensions

Model GPW + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Reduce Voltage Y-Delta Closed Starter

With ViZiTouch V2 operator interface

| Voltage | kW | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|-------------|---|-----|----|-------------|------|-----|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| 380-415 | 4-45 | 56 | 52 | 21 | 1422 | 1321 | 533 | 400 | 181 |
| | 55-110 | 62 | 60 | 23 | 1575 | 1524 | 584 | 700 | 318 |
| | 132 | 76 | 70 | 27 | 1930 | 1778 | 686 | 1050 | 476 |
| | 250 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1200 | 544 |
| | 315* | 76 | 100 | 27 | 1930 | 2540 | 686 | 850 | 386 |
| | 315 and up* | 76 | 112 | 27 | 1930 | 2845 | 686 | N/A | N/A |

*Consult factory for exact dimensions

This is a marketing document. Please consult factory for more information.



Shipping Weights and Dimensions

Model GPV

Electric Motor Driven Fire Pump Controller

Full Service

Reduced Voltage Primary Resistor Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|---------|---------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 220 | 100 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 350 | 159 |
| | 75-150 | 76 | 46 | 29 | 1930 | 1168 | 737 | 530 | 240 |
| | 200 | 76 | 70 | 29 | 1930 | 1778 | 737 | 650 | 295 |
| 220-240 | 5-30 | 56 | 36 | 21 | 1422 | 914 | 533 | 220 | 100 |
| | 40-60 | 62 | 40 | 23 | 1575 | 1016 | 584 | 350 | 159 |
| | 75-200 | 76 | 46 | 29 | 1930 | 1168 | 737 | 530 | 240 |
| | 250 | 76 | 70 | 29 | 1930 | 1778 | 737 | 650 | 295 |
| 380-415 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 310 | 141 |
| | 75-125 | 62 | 40 | 23 | 1575 | 1016 | 584 | 425 | 193 |
| | 150-300 | 76 | 46 | 29 | 1930 | 1168 | 737 | 765 | 347 |
| | 350-450 | 76 | 70 | 29 | 1930 | 1778 | 737 | 1800 | 816 |
| 440-480 | 5-60 | 56 | 36 | 21 | 1422 | 914 | 533 | 230 | 104 |
| | 75-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 380 | 172 |
| | 200-450 | 76 | 46 | 29 | 1930 | 1168 | 737 | 1900 | 862 |
| | 500 | 76 | 70 | 29 | 1930 | 1778 | 737 | 2000 | 907 |
| 600 | 5-75 | 56 | 36 | 21 | 1422 | 914 | 533 | 230 | 104 |
| | 100-150 | 62 | 40 | 23 | 1575 | 1016 | 584 | 450 | 204 |
| | 200-500 | 76 | 46 | 29 | 1930 | 1168 | 737 | 335 | 152 |

This is a marketing document. Please consult factory for more information.



Shipping Weights and Dimensions

Model GPV + GPU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Full Service

Reduced Voltage Primary Resistor Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|---------|---------|---|-------|-------|-------------|-------|-------|------------------------|-----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 208 | 5-30 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 40-60 | 62 | 60 | 23 | 1575 | 1524 | 584 | 510 | 231 |
| | 75-100 | 76 | 70 | 27 | 1930 | 1778 | 686 | 850 | 386 |
| | 125-150 | 76 | 76 | 27 | 1930 | 1930 | 686 | 850 | 386 |
| | 200 | 76 | 112 | 21 | 1930 | 2845 | 533 | 1150 | 522 |
| 220-240 | 5-30 | 56 | 52 | 23 | 1422 | 1321 | 584 | 345 | 156 |
| | 40-60 | 62 | 60 | 27 | 1575 | 1524 | 686 | 510 | 231 |
| | 75-125 | 76 | 70 | 27 | 1930 | 1778 | 686 | 900 | 408 |
| | 150-200 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1200 | 544 |
| | 250 | 76 | 112 | 27 | 1930 | 2845 | 686 | 1350 | 612 |
| 380-415 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 400 | 181 |
| | 75-125 | 62 | 60 | 23 | 1575 | 1524 | 584 | 700 | 318 |
| | 150-200 | 76 | 70 | 27 | 1930 | 1778 | 686 | 850 | 386 |
| | 250-300 | 76 | 76 | 27 | 1930 | 1930 | 686 | 850 | 386 |
| | 350 | 76 | 100 | 27 | 1930 | 2540 | 686 | 850 | 386 |
| | 400-450 | 76 | 112 | 27 | 1930 | 2845 | 686 | 850 | 386 |
| 440-480 | 5-60 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 75-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 570 | 259 |
| | 200-250 | 76 | 70 | 27 | 1930 | 1778 | 686 | 850 | 386 |
| | 300-450 | 76 | 76 | 27 | 1930 | 1930 | 686 | 850 | 386 |
| | 500 | 76 | 112 | 27 | 1930 | 2845 | 686 | 850 | 386 |
| 600 | 5-75 | 56 | 52 | 21 | 1422 | 1321 | 533 | 345 | 156 |
| | 100-150 | 62 | 60 | 23 | 1575 | 1524 | 584 | 600 | 272 |
| | 200-350 | 76 | 70 | 27 | 1930 | 1778 | 686 | 995 | 451 |
| | 400-500 | 76 | 76 | 27 | 1930 | 1930 | 686 | 1400 | 635 |

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPL

Electric Motor Driven Fire Pump Controller

Limited Service

Across The Line Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|----------------|-------|---|-------|-------|-------------|-------|-------|------------------------|----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 200-240 | 3-7.5 | 30 | 24 | 17 | 762 | 610 | 432 | 80 | 36 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |
| 208-240 | 3-7.5 | 30 | 24 | 17 | 762 | 610 | 432 | 80 | 36 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |
| 380-480 | 3-7.5 | 30 | 24 | 17 | 762 | 610 | 432 | 80 | 36 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |
| 600 | 3-7.5 | 30 | 24 | 17 | 762 | 610 | 432 | 80 | 36 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |

This is a marketing document. Please consult factory for more information.

Shipping Weights and Dimensions

Model GPL + GLU

Electric Motor Driven Fire Pump Controller

With Automatic Power Transfer Switch

Limited Service

Across The Line Starter

With ViZiTouch V2 Operator Interface

| Voltage | HP | Approx. Shipping Dimensions Height x Width x Depth | | | | | | Approx Shipping Weight | |
|---------|-------|---|-------|-------|-------------|-------|-------|------------------------|----|
| | | Inches | | | Millimeters | | | Lbs | Kg |
| | | Height | Width | Depth | Height | Width | Depth | | |
| 200-240 | 3-7.5 | 46 | 35 | 18 | 1168 | 889 | 457 | 180 | 82 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |
| 208-240 | 3-7.5 | 46 | 35 | 18 | 1168 | 889 | 457 | 180 | 82 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |
| 380-480 | 3-7.5 | 46 | 35 | 18 | 1168 | 889 | 457 | 180 | 82 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |
| 600 | 3-7.5 | 46 | 35 | 18 | 1168 | 889 | 457 | 180 | 82 |
| | 10 | | | | | | | | |
| | 15 | | | | | | | | |
| | 20 | | | | | | | | |
| | 25 | | | | | | | | |
| | 30 | | | | | | | | |

This is a marketing document. Please consult factory for more information.