

Certificate of Compliance

Issued to:

Tornatech FZE

PO Box 18435

Plot No S10131, Jebel Ali South

Dubai AE

TORNATECH INC

4100 Desserte Sud, (A-440 Ouest)

Laval

QC

CA

H7T 0H3

Certificate Number:

EX3971

Report Reference:

EX3971-20061111

Issue Date:

2024-04-03

This certificate confirms that representative samples of:

Please see the addendum for additional Product Information.

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

Please see the addendum for Standards of Safety.

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch

UL Mark Certification Program Owner

Certificate of Compliance

Certificate Number: EX3971
Report Reference: EX3971-20061111
Issue Date: 2024-04-03

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Addendum:

Product Covered:

USL, CNL Fire Pump Controllers, horsepower rated, Models GPA, GPP, GPR, GPS, GPV, GPY, or GPW; may be followed by a number 110 through 575 with - or /; followed by a number 200 through 600 with /; followed by a number 1 through 500 with /; followed by 1 or 3 with /; followed by 50 or 60 or 50/60.

USL, CNL Fire Pump Controllers, kilowatt rated, Models GPA, GPP, GPR, GPS, GPV, GPY, or GPW; followed by -380/or 400/ or 415/; followed by a number 0.75 through 560 with kW/; followed by 3 with /; followed by 50 or 60 or 50/60

USL, CNL Transfer Switches, horsepower rated, Models GPU; may be followed by a number 110 through 575 with - or /; followed by a number 200 through 600 with /; followed by a number 1 through 500 with /; followed by 1 or 3 with /; followed by 50 or 60 or 50/60.

USL, CNL Transfer Switches, kilowatt rated, Models GPU; followed by -380/or 400/ or 415/; followed by a number 0.75 through 560 with kW/; followed by 3 with /; followed by 50 or 60 or 50/60

USL, CNL Limited Service Fire Pump Controllers, horsepower rated, Models GPL; may be followed by a number 110 through 575 with - or /; followed by a number 200 through 600 with /; followed by a number 1 through 30 with /; followed by 1 or 3 with /; followed by 50 or 60 or 50/60.

USL, CNL Limited Service Fire Pump Controllers, kilowatt rated, Models GPL; followed by -380/or 400/ or 415/; followed by a number 0.75 through 22 with kW/; followed by 1 or 3 with /; followed by 50 or 60 or 50/60

USL, CNL Limited Service Transfer Switches, for connection to a second utility, horsepower rated, Models GLU; may be followed by a number 110 through 575 with - or /; followed by a number 200 through 600 with /; followed by a number 1 through 30 with /; followed by 1 or 3 with /; followed by 50 or 60 or 50/60.

Certificate of Compliance

Certificate Number: EX3971
Report Reference: EX3971-20061111
Issue Date: 2024-04-03

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Addendum:

Product Covered:

USL, CNL Limited Service Transfer Switches, for connection to a second utility, kilowatt rated, Models GLU; followed by -380/or 400/ or 415/; followed by a number 0.75 through 22 with kW/; followed by 1 or 3 with /; followed by 50 or 60 or 50/60

USL, CNL Fire Pump Controllers, horsepower rated, Models VPA or VPS; followed by a number 200 through 600 with /; followed by a number 5 through 450 with /; followed by 3 with /; followed by 50 or 60 or 50/60.

USL, CNL Fire Pump Controllers, kilowatt rated, Models VPA or VPS; followed by -380 through 415/; followed by a number 4 through 250 with kW/; followed by 3 with /; followed by 50 or 60 or 50/60.

USL, CNL Transfer Switches, horsepower rated, Models VPU; followed by a number 200 through 600 with /; followed by a number 5 through 450 with /; followed by 3 with /; followed by 50 or 60 or 50/60.

USL, CNL Fire Pump Controllers, kilowatt rated, Models VPU; followed by -380 through 415/; followed by a number 4 through 250 with kW/; followed by 3 with /; followed by 50 or 60 or 50/60.

Standards for Safety:

UL 218 / CSA C22.2 No. 263-15, Fire Pump Controllers, 3rd / 2nd Edition

UL 508, Industrial Control Equipment, 18th Edition

NFPA 20, Standard for the Installation of Stationary Pumps for Fire Protection

